

REINITIALIZE NODE 1 MDMs

1. VERIFY MDM STATES AND MDM IDs
- PCS2(1) Node 1: C&DH: MDM N1-2(1)
PRIMARY NCS MDM Node 1
- √STATE - Primary
√MDM ID - N1-2(1)
- PCS2(1) Node 1: C&DH: MDM N1-1(2)
SECONDARY NCS MDM Node 1
- √Frame Count - static
- PCS2(1) Node 1: C&DH: MDM N1-2(1)
PRIMARY NCS MDM Node 1
'Software Control'
- sel Transmit Mode Code
- Primary_NCS_Transmit_Mode_Code
- sel Primary NCS Xmt Mode Code Commands
cmd Xmt_Stat_Word_Tmplt
enter Bus ID - 2
enter RT Address - 6(5) **Execute**
- √Subsystem Flag Set - X (set)
- If Subsystem Flag Bit is set, N1-1(2) MDM is in Diagnostic State and is ready to accept diagnostic commands.
- If Reinitialize MDM from EEPROM, go to step 3.
|
If Reinitialize MDM from DRAM, go to step 2.
2. PERFORM MDM REINITIALIZATION FROM DRAM
- PCS2(1) Node 1: C&DH: MDM N1-2(1)
PRIMARY NCS MDM Node 1
'Software Control'
- sel MDM Utilities
sel Commands

NOTE

1. Startup process will execute from the UAS currently loaded in DRAM.
2. No POST is performed.

cmd N1_1(2)_MDM_Re_Init_MDM_DRAM Execute

Wait 60 seconds for MDM to reinitialize.
Go to step 4.

- PCS2(1)
3. PERFORM MDM REINITIALIZATION FROM EEPROM
Node 1: C&DH: MDM N1-2(1)

PRIMARY NCS MDM Node 1

'Software Control'

sel MDM Utilities
sel Commands

NOTE

1. Reinitialize MDM from EEPROM will cause the loss of all current information in the DRAM such as BST, current Bus, RT, and application configuration.
2. All UAS and default Configuration Tables will be loaded from EEPROM.
3. Normal POST will also be performed.

cmd N1_1(2)_MDM_Re_Init_MDM_EEPROM Execute

Wait 60 seconds for MDM to reinitialize.

- PCS2(1)
4. VERIFY MDM STATE AFTER REINITIALIZATION
Node 1: C&DH: MDM N1-1(2)

SECONDARY NCS MDM Node 1

√Frame Count - incrementing

'MDM Major State:'

√STATE - Standby

√MDM ID - N1-1(2)

```

*****
* If state is not Standby *
*                          *
*  ✓MCC                    *
*****

```

PCS2(1) 5. ENABLE NCS AUTO RETRY
 Node 1: C&DH: MDM N1-2(1)
PRIMARY NCS MDM Node 1
 'Software Control'

sel MDM Utilities
 ✓Primary_NCS_Auto_Retry_Ena - blank (Inhibited)

If X (Enable) >>

sel Commands
cmd Primary_NCS_Ena_NCS_Retry **Execute**

✓Primary_NCS_Auto_Retry_Ena - X (Enable)